



Technische gegevens:

Type	Flow l/min.	max. bar	Aansl.
DF5	60	350	3/8" G
DF10	90	350	1/2" G
DF20	140	350	3/4" G
DF25	220	350	1" G

3/2- Schuiven.

Type	Omschrijving:	Type
DF5/3A12L DF5/3B12L DF5/3A18L DF5/3A17C DF5/3B17C	arr. pos. 1 en 2, incl. handle arr. pos. 1 en 2, incl. handle veerret. pos. 2 , incl. handle rolbediend open / schakelen rolbediend gesloten / schakelen	DF10/3A12L DF10/3B12L DF10/3A17C DF10/3B17C
DF20/3A12L DF20/3B12L DF20/3A17C DF20/3B17C DF20/3A18PSLC	arr. pos. 1 en 2, incl. handle arr. pos. 1 en 2, incl. handle rolbediend open / schakelen rolbediend gesloten / schakelen pneum.bediend veerret. pos. 2.	DF25/3A12L DF25/3B12L DF25/3A17C DF25/3B17C

6/2-schuiven.

Type	Omschrijving:	Type
DF5/6A12L DF5/6B12L DF5/6B17PSLC	arr. pos. 1 en 2, incl. handle arr. pos. 1 en 2, incl. handle pneum.bediend veerret. pos. 1	DF10/6A12L DF10/6B12L
DF20/6A12L DF20/6B12L DF20/6B17PSLC	arr. pos. 1 en 2, incl. handle arr. pos. 1 en 2, incl. handle pneum.bediend veerret. pos. 1	